

Technical Specification

1/2" Super Flexible RF Coaxial Cable



1inner conductor 2insulation 3outer conductor 4jacket

Type		Type No.
Standard cable		HCAHY-50-9
Fire-retardant cable		HCAHYZ-50-9
Construction		
Inner conductor	Material	Copper clad aluminum wire
	Diameter (mm)	3.58±0.03
Insulation	Material	Foamed PE
	Diameter (mm)	9.30±0.20
Outer conductor	Material	Helical corrugated copper tube
	Diameter (mm)	12.0±0.15
Jacket	Material	LLDPE or fire-retardant PE
	Diameter (mm)	13.40±0.20
Mechanical Characteristics		
Bending radius (mm)	Single bend	25
	Repeated bend	55
Tensile strength (N)		750
Cable weight (kg/km)		135
Recommended temperature (°C)	Storage	-70~+85
	Installation	-40~+60
	Operating	-55~+85

Note:

For fire-retardant jackter cable, recommended temperature:

Storage: -30℃~+80℃

Installation: -25℃~+60℃

Operating temperature: -30℃~+80℃

Electrical Characteristics

Inner conductor DC resistance (Ω/km)		2.97
Outer conductor DC resistance (Ω/km)		6.50
Characteristic impedance (Ω)		50
Capacitance (p F/m)		83
Velocity (%)		81
Dielectric strength (KV)		3.0
Insulation resistance (MΩ/km)		>1×10 ⁴
Peak power rating (KW)		15.6
Peak voltage (V)		1400
Cut-off frequency (GHz)		17.0
Attenuation and Average power (Maximum attenuation value shall be 105% of the nominal attenuation value)		
Frequency (MHz)	Attenuation (@20℃, dB/100m)	Average power (kw)
200	4.84	2.17
450	7.59	1.38
800	10.42	1.01
900	11.21	0.95
1000	11.82	0.89
1500	14.59	0.68
1800	16.01	0.63
2000	17.22	0.60
2200	18.21	0.56
2500	19.62	0.53
3000	22.31	0.46
VSWR		
800MHz~1000MHz		1.10
1700MHz~2500MHz		1.13
2500MHz~3000MHz		1.15

● Products meet the RoHS requirement, and according to the requirements of RoHS, you can see the RoHS mark on the outside package.