


Customer: _____

Topsignal Type: SMT680-063T

Customer P/N: _____

Specification No.: SR063T-001

**Construction Specification / 结构尺寸**

Item/项目	Material/材料	Diameter/直径(mm)
1 . Inner conductor/内导体	Silver plated copper clad steel/镀银铜包钢线	0.40±0.02
2 . Dielectric/绝缘	PTFE/聚四氟乙烯	1.30±0.05
3 . Outer conductor/外导体	Tin plated seamless copper tube/镀锡无缝退火紫铜管	1.60±0.05

Electrical Characteristics/电气性能

Capacitance/电容(pF/m)	Nom. 95.1
Impedance/阻抗(ohm)	50
Velocity/速率(%)	69.5
Corona extinction voltage/灭晕电压(kVrms 50Hz)	1.0
Cutoff frequency/截止频率(GHz)	85

Mechanical and Environmental Characteristics/机械和环境性能

Operating temp./工作温度(°C)	-55 to 125
Min. bending radius static/最小弯曲半径, 单次(mm)	5.6
RoHS/RoHS环保	Compliant/符合

Attenuation @ 20°C and Sea Level, Power/海平面 20°C 衰减, 功率

Frequency(GHz)	Attenuation(dB/m)	Average Power(W)
0.5	0.573	103.8
1.0	0.804	72.8
5.0	1.872	31.4

Revision Number: 1.0

Revision Date: 2011-4-11 17:44:48

制作: song _____

审核: _____

批准: _____