

半柔射频同轴电缆规格书

Semi-flexible RF Coaxial Cable Specification

规格Cable Type: SFX-141/61 FEP



嘉兴市弘讯电子有限公司

Jiaxing topsignal Electronics Co., Ltd.

版权所有 侵权必究

All rights reserved

修订记录

Document update record

日期 Date	修订人 Reviser	审核人 Author	版本 Revision	修订声明 Revision declaration
			V1.0	First version

目录

Contents

1 基本要求 Basic Requirement.....4

2 外观/结构 Appearance/ Construction4

3 类型和规格 Type and Spec.....4

4 标记信息 Marking Information5

5 电气性能 Electrical Characteristics.....5

6 物理、机械性能 Mechanical and Physical Characteristics6

7.包装存储运输要求 Packaging, Storage, Transportation..... 6


8.产品应用 Application..... 6

1 基本要求Basic Requirement

工作温度范围 Working temperature range	-65℃～200℃
安装温度 Working humidity range	-20℃～80℃
贮存温度 Storage temperature	-65℃～200℃
使用寿命 Service life	≥3 years
参考依据 Reference standards	IEC61196-8

2 外观/结构Appearance/ Construction

2.1 轮廓图 Outline Drawing



3 类型和规格Type and Specs

3.1 内导体 Inner Conductor

材料 Material: 镀银铜线 Silver-plated Copper
内导体直径（包含公差） Inner Conductor Diameter (with tolerance): 0.73 mm±0.01 mm

3.2 绝缘体 Insulation

材料 Material: 聚四氟乙烯 PTFE
绝缘体直径（包含公差） Insulation Diameter (with tolerance): 3.00 mm±0.05 mm

3.3 外导体 Out Conductor

材料 Material: 浸锡铜线编织 Tinned Soaked Copper Wire Braid
外导体直径（包含公差） Outer Conductor Diameter (with tolerance): 3.52 mm±0.10 mm

3.4 外护套 Outer Jacket

材料 Material: 聚全氟乙丙烯 FEP

外护套直径 Outer Jacket Diameter: 4.15 mm±0.10 mm

平均厚度 Average Thickness: 0.31 mm

4 标记信息 Marking Information

无印字

5 电气性能 Electrical Characteristics

5.1 内导体直流电阻 Inner Conductor DC Resistance

$\leq 45 \Omega/\text{km}@20^{\circ}\text{C}$

5.2 外导体直流电阻 Outer Conductor DC Resistance

$\leq 16 \Omega/\text{km}@20^{\circ}\text{C}$

5.3 绝缘电阻 Insulation Resistance

$\geq 5000 \text{ M}\Omega \cdot \text{km}$

5.4 介质耐压 Dielectric Strength

DC 5000 V 1 min: No crack

5.5 特性阻抗 Characteristic Impedance

$61 \Omega \pm 3 \Omega$

5.6 传输速率 Velocity

70.8%

5.7 屏蔽效率 Shielding Effectiveness

$>100 \text{ dB @ } 1\text{GHz}$

5.8 海平面20℃下衰减和40℃环境温度下的平均功率Nominal attenuation @20℃ and sea

level mean power rating at 40℃ (104°F) ambient temperature.

Freq(MHz)	Attenuation Typical (dB/m)	Mean Power(W)
500	0.29	410
1000	0.41	290

5.9 电容 (参考) Mutual Capacitance (refer)

77±3 pF/m

5.10 峰值射频电压 Peak RF Voltage Rating

1.9 kv

5.11 延时 Delay

4.7ns/m

6 物理、机械性能 Mechanical and Physical Characteristics

6.1 最小单次弯曲半径 Min. Single Bending Radius

8mm

6.2 最小重复弯曲半径 Min. Repeated Bending Radius

40mm*20 cycles

6.3 重量 Weight

Nom.48 g/m

6.4 环保 Environment Compliant

RoHS

REACH

6.5 阻燃 Flammability

IEC 60332-3-24

VW-1

7.包装存储运输要求 Packaging, Storage, Transportation

7.1 包装 Packaging

胶盘+纸箱包装约 265 米/盘 plastic spool + carton box, about 265m/spool.

7.2 存储要求 Storage Requirements

存储温度为 $10^{\circ}\text{C} \sim +35^{\circ}\text{C}$ ，相对湿度 $\leq 80\%$ ，周围空气中无酸性、碱性等腐蚀性气体。

Temperature $10^{\circ}\text{C} \sim +35^{\circ}\text{C}$, relative humidity $\leq 80\%$, the surrounding air without acid, alkaline and other corrosive gases

7.3 运输搬运过程中不要剧烈振动或碰撞.

Don't be violent vibration and impact during transportation or carrying.

8. 产品应用 Application

通信基站天线系统 Telecommunications antenna system