

半柔射频同轴电缆规格书

Semi-flexible RF Coaxial Cable Specification

规格Cable Type: SFX-141/75 FEP



嘉兴市弘讯电子有限公司

Jiaxing topsignal Electronics Co., Ltd.

版权所有 侵权必究

All rights reserved

修订记录

Document update record

日期 Date	修订人 Reviser	审核人 Author	版本 Revision	修订声明 Revision declaration
2019-04-01			V1.0	First version

目录

Contents

1 基本要求 Basic Requirement.....4

2 外观/结构 Appearance/ Construction4

3 类型和规格 Type and Spec.....4

4 标记信息 Marking Information5

5 电气性能 Electrical Characteristics.....5

6 物理、机械性能 Mechanical and Physical Characteristics6

7.包装存储运输要求 Packaging, Storage, Transportation..... 6


8.产品应用 Application..... 6

1 基本要求Basic Requirement

工作温度范围 Working temperature range	-65℃～200℃
安装温度 Working humidity range	-20℃～80℃
贮存温度 Storage temperature	-65℃～200℃
使用寿命 Service life	≥3 years
参考依据 Reference standards	IEC61196-8

2 外观/结构Appearance/ Construction

2.1 轮廓图 Outline Drawing



3 类型和规格Type and Specs

3.1 内导体 Inner Conductor

材料 Material:镀银铜合金线 Silver Plated Copper Alloy Wire
内导体直径（包含公差）Inner Conductor Diameter (with tolerance): 0.53 mm±0.01 mm

3.2 绝缘体 Insulation

材料 Material: 聚四氟乙烯 PTFE
绝缘体直径（包含公差）Insulation Diameter (with tolerance): 3.00 mm±0.05 mm

3.3 外导体 Out Conductor

材料 Material: 浸锡铜线编织 Tinned Soaked Copper Wire Braid
外导体直径（包含公差）Outer Conductor Diameter (with tolerance): 3.52 mm±0.10 mm

3.4 外护套 Outer Jacket

材料 Material: 聚全氟乙丙烯 FEP

外护套直径 Outer Jacket Diameter: 4.15 mm±0.10 mm

平均厚度 Average Thickness: 0.31 mm

4 标记信息 Marking Information

无印字

5 电气性能 Electrical Characteristics

5.1 内导体直流电阻 Inner Conductor DC Resistance

$\leq 90 \Omega/\text{km}@20^{\circ}\text{C}$

5.2 外导体直流电阻 Outer Conductor DC Resistance

$\leq 16 \Omega/\text{km}@20^{\circ}\text{C}$

5.3 绝缘电阻 Insulation Resistance

$\geq 5000 \text{ M}\Omega\cdot\text{km}$

5.4 介质耐压 Dielectric Strength

DC 5000 V 1 min: No crack

5.5 特性阻抗 Characteristic Impedance

$75 \Omega \pm 3 \Omega$

5.6 传输速率 Velocity

70.8%

5.7 截止频率 Cut-off Frequency

38 GHz

5.8 屏蔽效率 Shielding Effectiveness

$>100 \text{ dB @ } 1\text{GHz}$

5.9 海平面20℃下衰减和40℃环境温度下的平均功率 Nominal attenuation @20℃ and sea level mean power rating at 40℃ (104°F) ambient temperature.

Freq(MHz)	Attenuation Typical (dB/m)	Mean Power(W)
500	0.28	549
1000	0.40	382
5000	0.97	160
10000	1.45	108
20000	2.21	72

5.10 电容 (参考) Mutual Capacitance (refer)

62±3 pF/m

5.11 三阶交调 Intermodulation 3rd order

<-120 dBm(900 MHz/1800 MHz/2100MHz/2600MHz @2*43dBm)

5.12 峰值射频电压 Peak RF Voltage Rating

1.9 kv

5.13 相位差 Phase Difference:

1440° ±4° @△l= 425 mm±0.1 mm @ 2 GHz

5.14 延时 Delay

4.7ns/m

6 物理、机械性能 Mechanical and Physical Characteristics

6.1 最小单次弯曲半径 Min. Single Bending Radius

8mm

6.2 最小重复弯曲半径 Min. Repeated Bending Radius

40mm*20 cycles

6.3 重量 Weight

Nom.43.8g/m

6.4 环保 Environment Compliant

RoHS

REACH

6.5 阻燃 Flammability

IEC 60332-3-24

VW-1

7.包装存储运输要求 Packaging, Storage, Transportation

7.1 包装 Packaging

胶盘+纸箱包装约 265 米/盘 plastic spool + carton box, about 265m/spool.

7.2 存储要求 Storage Requirements

存储温度为 $10^{\circ}\text{C} \sim +35^{\circ}\text{C}$ ，相对湿度 $\leq 80\%$ ，周围空气中无酸性、碱性等腐蚀性气体。

Temperature $10^{\circ}\text{C} \sim +35^{\circ}\text{C}$, relative humidity $\leq 80\%$, the surrounding air without acid, alkaline and other corrosive gases

7.3 运输搬运过程中不要剧烈振动或碰撞.

Don't be violent vibration and impact during transportation or carrying.

8. 产品应用 Application

通信基站天线系统 Telecommunications antenna system