


产品规格 Product Type		TSA-360			
结构图 Structure Drawing					
结构特性 Structure Characteristics					
结构 Structure	项目 Item	标准值 Standard Value			
内导体 Inner Conductor	材质 Material	镀银铜线 Silverplated Copper Wire			
	结构 Construction(mm)	1/0.91			
	标称外径 Nom.Dia(mm)	0.91±0.02			
绝缘层 Insulation	材质 Material	低密度聚四氟乙烯 LD-PTFE			
	标称外径 Nom.Dia(mm)	2.50±0.05			
外导体 Outer Conductor	材质 Material	镀银铜带 Silverplated Copper Strip			
	标称外径 Nom.Dia(mm)	2.70±0.05			
	材质 Material	镀银铜线 Silverplated Copper Wire			
	标称外径 Nom.Dia(mm)	3.20±0.05			
护套 Jacket	材质 Material	聚全氟乙丙烯 FEP 灰色			
	标称外径 Nom.Dia(mm)	3.60±0.10			
电气性能 Electrical Characteristics					
项目 Item	标准值 Standard Value	项目 Item	频率 (MHz)	dB/100m	kw
阻抗 Impedanc (Ω)	50±2	衰减 Attenuation (25℃ 室 温) (dB/100m) 功率 Power (室温, 海平 面, 驻波 1.1) kw	900	35.55	0.540
电容 Capacitance(pF/m)	81.4		1000	37.50	0.511
			1500	46.08	0.416
			2000	53.36	0.359
速率 Velocity(%)	82		3000	65.65	0.292
			4000	76.10	0.252
峰值功率 Max Power (KW)	2.0		5000	85.37	0.225
			6000	93.81	0.204
最大工作电压 Max.Operating Voltage(V)	900 DC		8000	108.91	0.176
			10000	122.35	0.157
截止频段 Cutoff Frequency(GHz)	46		12000	134.6	0.142
			12400	136.94	0.140
介电常数 Dielectric constant	1.49		13500	143.19	0.134
			15000	151.36	0.127
时延 Time delay (nS/m)	4.06		18000	166.67	0.115
			24000	194.22	0.099
重量 Weight (g)	36		26500	204.79	0.094
			40000	255.69	0.075
可靠性 Dependability					
最小弯曲半径(单次)Min.Bending Radius/Single		mm	18		
最小弯曲半径 (重复) Min.Bending Radius/Repeated		mm	36		
工作温度范围 Operating Temperature		℃	-55-+165		
使用提示 Trips for Use					
存储环境 Storage Environment		温度: 30℃以下, 湿度: 20-65%			
同类产品替换 Similar Cable to Replace					
电缆型号 Cable Type		可替代型号 Replaceable Type			
TSA-360		CXN3507			

