

MIL-C-17 美军标射频同轴电缆 Radio frequency coaxial cable MIL RG series

RG6



- | | |
|-----------------------|-----------------------|
| 1.内导体 Inner Conductor | 2.绝缘 Insulation |
| 3.外导体 Outer Conductor | 4.外导体 Outer Conductor |
| 5.护套 Jacket | |

电缆结构/Construction

内导体 Inner Conductor	铜线 BC Wire	1.00±0.02
绝缘 Insulation	发泡聚乙烯 Physical foaming PE	4.57±0.15
外导体 Outer Conductor	铝箔 Al-PET Foil	4.77±0.15
	编织线 Braiding Wire	5.25±0.15
护套 Jacket	聚氯乙烯 PVC	6.90±0.20

机械性能/Mechanical Characteristics

弯曲半径(mm) Bending Radius	单次 Single	35
	多次 Repeated	70
耐温等级 Temperature	℃	-40~+75

环境负荷物质应对情况/Environment-Friendliness

RoHS 指令/2011/65/EU	满足/ Compliant
--------------------	---------------

电气性能/Electrical Characteristics

特性阻抗/Impedance	Ω	75±2
绝缘电阻 Insulation Resistance	MΩ · km	>5×10 ³
绝缘耐压强度 Dielectric Strength	KV	1.6
护套耐压强度 Jacket Strength	KV	浸水 (flooding) 2.0
		火花 (spark) 3.0
回波损耗 Return Loss	dB	VHF≥20
		UHF≥20
屏蔽衰减 Screening Attenuation	dB	55MHz ≥60
		300MHz ≥70
		1000MHz ≥70
衰减 Attenuation@20℃	dB/100m	55MHz 5.25
		211MHz 11.10
		270MHz 11.48
		300MHz 12.14
		330MHz 12.76
		400MHz 14.11
		450MHz 15.03
		550MHz 16.70
		750MHz 19.69
		870MHz 21.33
		1000MHz 22.97