

TSR 系列射频同轴电缆 Radio frequency coaxial cable LMR series

TSR200



- | | |
|-----------------------|-----------------------|
| 1.内导体 Inner Conductor | 2.绝缘 Insulation |
| 3.外导体 Outer Conductor | 4.外导体 Outer Conductor |
| 5.护套 Jacket | |

电缆结构/Construction

内导体 Inner Conductor	铜线或铜包钢线 BC or CCS Wire	1.12±0.02
绝缘 Insulation	发泡聚乙烯 Physical foaming PE	2.95±0.10
外导体 Outer Conductor	铝箔 Al-PET Foil	3.07±0.10
	编织线 Braiding Wire	3.66±0.10
护套 Jacket	聚氯乙烯或聚乙烯 PVC or PE	4.95±0.10

机械性能/Mechanical Characteristics

弯曲半径(mm) Bending Radius	单次 Single	25
	多次 Repeated	50
耐温等级 Temperature	℃	-40~+75

环境负荷物质应对情况/Environment-Friendliness

RoHS 指令/2011/65/EU	满足/ Compliant
--------------------	---------------

电气性能/Electrical Characteristics

特性阻抗/Impedance	Ω	50±2
绝缘电阻 Insulation Resistance	MΩ · km	>5×10 ³
绝缘耐压强度 Dielectric Strength	KV	1.6
护套耐压强度 Jacket Strength	KV	浸水 (flooding) 2.0
		火花 (spark) 3.0
回波损耗 Return Loss	dB	VHF≥20
		UHF≥20
屏蔽衰减 Screening Attenuation	dB	≥90
衰减 Attenuation@20℃	dB/100m	30MHz 5.8
		50MHz 7.5
		150MHz 13.1
		220MHz 15.9
		450MHz 22.8
		900MHz 32.6
		1500MHz 42.4
		1800MHz 46.6
		2000MHz 49.3
		2500MHz 55.4
		5800MHz 86.5